

# WIRE NAIL & DRILLING MACHINES



## WIRE NAIL MACHINE

	MEWN-1A	MEWN-1	MEWN-2	MEWN-3	MEWN-4	MEWN-5	MEWN-6
CAPACITY	6-25mm 1/4"-1"	12-38mm 1/2"-1 1/2"	12-50mm 1/2"-2"	20-75mm 3/4"-3"	25-100mm 1"-4"	50-150mm 2"-6"	50-200mm 2"-8"
WIRE	0.9-1.4mm 20-17SWG	1.2-2mm 18-14SWG	1.6-2.6mm 16-12SWG	2.3-7mm 14-9SWG	2.6-4mm 12-8SWG	4-9mm 8-6SWG	4-6mm 8-4WSG
NAIL PER MINUTE	500-550	400-450	300-350	225-275	175-210	100-125	90-100
MOTOR H.P.	1 X 1440	1.1/2X1440	2 X 1440	3 X 1440	5 X 1440	7.5 X 960	10 X 960

## ALL GEARED RADIAL DRILLING MACHINE

	MERD-40A	MERD-50B	MERD-65B
Drilling Capacity (in steel)	40	50	65
Drilling Depth	180	225	305
Taper Spindle Nose Socket	M.T. 4	M.T. 5	M.T. 5
No. of Spindle Speeds	6	9	12
RPM of the Spindle	45-660	40-790	18-810
Range of Spindle Feeds	.05-15mm/rev	.05-1.25mm/rev	.12-1.15mm/rev
Motor H.P.	2 HP	3 HP	5 H.P.
Drilling Radius			
Maximum / Minimum	1050 / 550	1100 / 450	1600 / 575
Drilling Head Traverse	800	900	1025
Distance Base Plate to Spindle			
Maximum / Minimum	1000 / 200	1300 / 400	1500 / 475
Working Surface of Base Plate			
Length / Width	800 / 550	915 / 660	1320 / 865
Arm Elevating Motor	1 HP	2 HP	3 HP

